



CMF / CRF Details

CMF ID: 10849

Convert intersection to restricted crossing U-turn (RCUT) intersection

Description: The RCUT, also referred to as the superstreet intersection or J-turn intersection. The conversion is for either signalized or stop-controlled.

Prior Condition: Signalized Intersection

Category: Intersection geometry

Study: [*Evaluating the Safety Effectiveness of Restricted Crossing U turn \(RCUT\) Intersections, Mishra and Pulugurtha, 2021*](#)

Star Quality Rating	
Star Quality Rating:	

Crash Modification Factor (CMF)

Value:	0.689
Adjusted Standard Error:	
Unadjusted Standard Error:	0.198

Crash Reduction Factor (CRF)

Value:	31.08 (This value indicates a decrease in crashes)
Adjusted Standard Error:	

Unadjusted Standard Error:	19.83
-----------------------------------	-------

Applicability

Crash Type:	All
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	Suburban
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	4-leg
Traffic Control:	Stop-controlled
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	
Municipality:	
State:	NC

Country:	
Type of Methodology Used:	2
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jul-01-2021
Comments:	This CMF is for installation of Signalized RCUT.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.