



CMF / CRF Details

CMF ID: 2129

Install bicycle tracks

Description: Bicycle tracks are about 2-2.5 meters wide.

Prior Condition: No bike facilities

Category: Bicyclists

Study: [*Bicycle Tracks and Lanes: a Before-After Study, Jensen, 2008*](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.97

Adjusted Standard Error:

Unadjusted Standard Error: 0.115

Crash Reduction Factor (CRF)

Value: 3 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error: 10.6

Applicability

Crash Type: Single vehicle

Crash Severity: All

Roadway Types: Not Specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type:

Traffic Volume: 5000 to 28000 *Average Daily Traffic (ADT)*

Time of Day: All

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used: 1976 to 2004

Municipality: Copenhagen, Denmark

State:

Country:

Type of Methodology Used:	3
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.