



CMF / CRF Details

CMF ID: 2356

Install TWLTL (two-way left turn lane) on two lane road

Description:

Prior Condition: *No Prior Condition(s)*

Category: Roadway

Study: [*Safety Evaluation of Installing Center Two-Way Left-Turn Lanes on Two-Lane Roads, Lyon et al., 2008*](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.833

Adjusted Standard Error:

Unadjusted Standard Error: 0.105

Crash Reduction Factor (CRF)

Value: 16.7 (*This value indicates a **decrease** in crashes*)

Adjusted Standard Error:

Unadjusted Standard Error:	10.5
-----------------------------------	------

Applicability

Crash Type:	All
Crash Severity:	All
Roadway Types:	Not Specified
Number of Lanes:	2
Road Division Type:	Divided by TWLTL
Speed Limit:	
Area Type:	Rural
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	1990 to 2004
Municipality:	
State:	IL

Country:	
Type of Methodology Used:	2
Sample Size Used:	
Before Sample Size Used:	36
After Sample Size Used:	36

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.