



CMF / CRF Details

CMF ID: 2690

Implement automated speed enforcement cameras

Description:

Prior Condition: media coverage of automated speed enforcement

Category: Advanced technology and ITS

Study: [Estimating the Longer-Term Safety Effects of Speed Enforcement Cameras in Charlotte, NC, Moon and Hummer, 2010](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.85

Adjusted Standard Error:

Unadjusted Standard Error: 0.11

Crash Reduction Factor (CRF)

Value: 15.1 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:	11.3
-----------------------------------	------

Applicability

Crash Type:	All
Crash Severity:	K (fatal),A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Not Specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	1994 to 2008
Municipality:	Charlotte
State:	NC

Country:	
Type of Methodology Used:	3
Sample Size Used:	
Before Sample Size Used:	17063
After Sample Size Used:	2002

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Aug-11-2010
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.