



CMF / CRF Details

CMF ID: 320

Install a traffic signal

Description:

Prior Condition: *No Prior Condition(s)*

Category: Intersection traffic control

Study: [NCHRP Report 491: Crash Experience Warrant for Traffic Signals, McGee et al., 2003](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.33

Adjusted Standard Error: 0.24

Unadjusted Standard Error: 0.2

Crash Reduction Factor (CRF)

Value: 67 (This value indicates a **decrease** in crashes)

Adjusted Standard Error: 24

Unadjusted Standard Error:

20

Applicability

Crash Type:

Angle

Crash Severity:

K (fatal),A (serious injury),B (minor injury),C (possible injury)

Roadway Types:

Not specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type:

Urban

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Roadway/roadway (not interchange related)

Intersection Geometry:

4-leg

Traffic Control:

Stop-controlled

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State:

Country:	
Type of Methodology Used:	2
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	Countermeasure name has been slightly modified for consistency across Clearinghouse

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.