



CMF / CRF Details

CMF ID: 4584

Convert right shoulder width from 8-ft to 6-ft

Description: Convert right shoulder width from 8-ft to 6-ft

Prior Condition: 8 ft wide shoulder

Category: Shoulder treatments

Study: [Accident Modification Factors for Traffic Engineering and ITS Improvements, Harkey et al., 2008](#)

Star Quality Rating:	

Crash Modification Factor (CMF)

Value:	1.04
Adjusted Standard Error:	
Unadjusted Standard Error:	

Crash Reduction Factor (CRF)

Value:	-4 (This value indicates an increase in crashes)
Adjusted Standard Error:	

Unadjusted Standard Error:

Applicability

Crash Type:

All

Crash Severity:

Not specified

Roadway Types:

Principal Arterial Other

Number of Lanes:

Multilane

Road Division Type:

Divided by Median

Speed Limit:

Area Type:

Rural

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State:

Country:	
Type of Methodology Used:	11
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	
Date Added to Clearinghouse:	Dec-01-2009
Comments:	HSM 1st Ed, Table 13-8

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.