



CMF / CRF Details

CMF ID: 5315

Install centerline and shoulder rumble strips

Description: Milled or rolled rumble strips.

Prior Condition: No Rumble Strips

Category: Roadway

Study: [Performance Analysis of Centerline and Shoulder Rumble Strips Installed in Combination in Washington State, D. Olson, M. Sujka, and B. Manchas, 2013](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.425

Adjusted Standard Error:

Unadjusted Standard Error: 0.179

Crash Reduction Factor (CRF)

Value: 57.5 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:	17.9
-----------------------------------	------

Applicability

Crash Type:	Head on,Sideswipe
--------------------	-------------------

Crash Severity:	K (fatal),A (serious injury)
------------------------	------------------------------

Roadway Types:	Not specified
-----------------------	---------------

Number of Lanes:	2
-------------------------	---

Road Division Type:	
----------------------------	--

Speed Limit:	
---------------------	--

Area Type:	Rural
-------------------	-------

Traffic Volume:	
------------------------	--

Time of Day:	Not specified
---------------------	---------------

If countermeasure is intersection-based

Intersection Type:	
---------------------------	--

Intersection Geometry:	
-------------------------------	--

Traffic Control:	
-------------------------	--

Major Road Traffic Volume:	
-----------------------------------	--

Minor Road Traffic Volume:	
-----------------------------------	--

Development Details

Date Range of Data Used:	2002 to 2010
---------------------------------	--------------

Municipality:	
----------------------	--

State:	WA
---------------	----

Country:	
Type of Methodology Used:	3
Sample Size Used:	
Before Sample Size Used:	29
After Sample Size Used:	7

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-02-2013
Comments:	Exposure presented as VMTBefore MVMT = 1,341.7After MVMT = 765.96Crash type is fatal and injury cross centerline crashes

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.