



CMF / CRF Details

CMF ID: 585

Introduce TWLTL (two-way left turn lanes) on rural two lane roads

Description:

Prior Condition: *No Prior Condition(s)*

Category: Roadway

Study: [*Safety Evaluation of Installing Center Two-Way Left-Turn Lanes on Two-Lane Roads, Persaud et al., 2008*](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.53

Adjusted Standard Error:

Unadjusted Standard Error: 0.04

Crash Reduction Factor (CRF)

Value: 47 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

4

Applicability

Crash Type:

Rear end

Crash Severity:

All

Roadway Types:

Not specified

Number of Lanes:

2

Road Division Type:

Speed Limit:

Area Type:

Rural

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State:

Country:	
Type of Methodology Used:	2
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.