



## CMF / CRF Details

**CMF ID: 6140**

### Installation of fixed speed cameras

**Description:** Installation of fixed speed cameras on arterials limited access freeways

**Prior Condition:** No Speed Cameras Present

**Category:** Speed management

**Study:** [\*An evaluation of the traffic safety effect of fixed speed cameras, De Pauw et al., 2014\*](#)

Star Quality Rating:



### Crash Modification Factor (CMF)

**Value:** 0.9

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 0.087

### Crash Reduction Factor (CRF)

**Value:** 10 (This value indicates a **decrease** in crashes)

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 8.7

### Applicability

**Crash Type:** All

**Crash Severity:** K (fatal),A (serious injury),B (minor injury),C (possible injury)

**Roadway Types:** Not specified

**Number of Lanes:** 1 to 2

**Road Division Type:**

**Speed Limit:** 30 - 55 mph (50 - 90 km/hr)

**Area Type:** All

**Traffic Volume:**

**Time of Day:** All

### *If countermeasure is intersection-based*

**Intersection Type:**

**Intersection Geometry:**

**Traffic Control:**

**Major Road Traffic Volume:**

**Minor Road Traffic Volume:**

### Development Details

**Date Range of Data Used:** 2000 to 2008

**Municipality:** Flanders

**State:**

<b>Country:</b>	Belgium
<b>Type of Methodology Used:</b>	1
<b>Sample Size Used:</b>	

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Mar-11-2015
<b>Comments:</b>	This CMF addresses all injury crashes within 500 meters of the speed camera location in both directions and includes the effect of other measures implemented with the camera, including: a decrease in the legally imposed speed limit, resurfacing, or changes in bicyclist or pedestrian facilities. The number of crashes in the after period were not reported in this study, however, they have been recorded as 300 to give 10 points as a benefit of doubt for one or more of the following: (1) number of miles/sites in the reference/treatment group, (2) number of crashes in the references/treatment group, (3) reporting AADTs for the aggregate dataset but not for the disaggregate dataset used for CMF development.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*