



CMF / CRF Details

CMF ID: 6791

Widen shoulder

Description:

Prior Condition: Narrower paved shoulder than after condition

Category: Shoulder treatments

Study: [*Safety Impacts of Highway Shoulder Attributes in Illinois, Bamzai et al., 2011*](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.83

Adjusted Standard Error:

Unadjusted Standard Error:

Crash Reduction Factor (CRF)

Value: 17 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

Applicability

Crash Type:

Fixed object,Head on,Run off road,Sideswipe

Crash Severity:

K (fatal)

Roadway Types:

Principal Arterial Interstate

Number of Lanes:

Road Division Type:

Divided by Median

Speed Limit:

45-65

Area Type:

Urban

Traffic Volume:

Time of Day:

All

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

2000 to 2006

Municipality:

State:

IL

Country:	USA
Type of Methodology Used:	2
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jun-22-2015
Comments:	This CMF applies to urban interstates with a lane width less than or equal to 12 ft. This CMF applies to shoulder related crashes, defined as head-on, fixed object, sideswipe opposite direction, and run-off-road.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.