



CMF / CRF Details

CMF ID: 8320

increase intersection illuminance from low (< 0.2 fc) to medium (≥ 0.2 fc and

Description: Increase intersection illuminance 13 from low (< 0.2 fc) to medium (≥ 0.2 fc and

Prior Condition: Signalized intersections with lower illuminance (

Category: Highway lighting

Study: [Safety Effects of Street Illuminance at Urban Signalized Intersections in Florida, Wei et al., 2016](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.47

Adjusted Standard Error:

Unadjusted Standard Error:

Crash Reduction Factor (CRF)

Value: 53 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

Applicability

Crash Type: Nighttime

Crash Severity: All

Roadway Types: Not specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type: Urban

Traffic Volume:

Time of Day: Night

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry: 3-leg

Traffic Control: Signalized

Major Road Traffic Volume: 5167 to 67508 Annual Average Daily Traffic (AADT)

Minor Road Traffic Volume: 1300 to 56387 Annual Average Daily Traffic (AADT)

Development Details

Date Range of Data Used: 2010 to 2013

Municipality: Tampa

State: FL

Country:	
Type of Methodology Used:	7
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jan-17-2017
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.