



CMF / CRF Details

CMF ID: 8988

Provide 2-ft paved shoulders (both sides)

Description: Provide 2-ft paved shoulders on both sides of 2-lane rural roads

Prior Condition: *No Prior Condition(s)*

Category: Shoulder treatments

Study: [Estimating Crash Modification Factors Using Cross-Sectional and Case-Control Methods for Rumble Strips and Paved Shoulders, Galgamuwa and Dissanayake, 2017](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.88

Adjusted Standard Error:

Unadjusted Standard Error: 0.019

Crash Reduction Factor (CRF)

Value: 12 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:	1.9
-----------------------------------	-----

Applicability

Crash Type:	Head on,Run off road,Sideswipe
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	2
Road Division Type:	Undivided
Speed Limit:	
Area Type:	Rural
Traffic Volume:	30 to 15900 <i>Annual Average Daily Traffic (AADT)</i>
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	2009 to 2014
Municipality:	
State:	KS

Country:	USA
Type of Methodology Used:	7
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Nov-17-2017
Comments:	Tangent segments; Lane departure crashes

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.